

1. VESSEL DESCRIPTION	
1.1	Date updated: Feb 17, 2010
1.2	Vessel's name: Hellespont Promise
1.3	IMO number: 9351438
1.4	Vessel's previous name(s) and date(s) of change: Not Applicable
1.5	Date delivered: Jan 02, 2007
1.6	Builder (where built): NEW CENTURY SHIPBUILDING Co. LTD-China
1.7	Flag: Liberia
1.8	Port of Registry: Monrovia
1.9	Call sign: A8IR2
1.10	Vessel's satcom phone number: 764645470
	Vessel's fax number: 764645467
	Vessel's telex number: 463791641-PROM
	Vessel's email address: fprom@hellesponthammonia.de
1.11	Type of vessel: Oil Tanker
1.12	Type of hull: Double Hull
Classification	
1.13	Classification society: American Bureau of Shipping
1.14	Class notation: +A1(E), Oil Carrier, (E), +AMS, +ACCU, VEC, SH, SHCM,FL(30),VEC,IGS,COW,UWILDS,ESP
1.15	If Classification society changed, name of previous society: N/A
1.16	If Classification society changed, date of change: Not Applicable
1.17	IMO type, if applicable: N/A
1.18	Does the vessel have ice class? If yes, state what level: No,
1.19	Date / place of last dry-dock: Not Applicable New vessel
1.20	Date next dry dock due: Jan 01, 2012
1.21	Date of last special survey / next survey due: Jan 02, 2007 Jan 01, 2012
1.22	Date of last annual survey: Nov 29, 2009
1.23	If ship has Condition Assessment Program (CAP), what is the latest overall rating: 0
1.24	Does the vessel have a statement of compliance issued under the provisions of the Condition Assessment Scheme (CAS): If yes, what is the expiry date? N/A
Dimensions	
1.25	Length Over All (LOA): 228.6 Metres
1.26	Length Between Perpendiculars (LBP): 219.7 Metres
1.27	Extreme breadth (Beam): 32.29 Metres
1.28	Moulded depth: 20.8 Metres
1.29	Keel to Masthead (KTM) / KTM in collapsed condition (if applicable): 48.765 Metres Metres
1.30	Bow to Center Manifold (BCM) / Stern to Center Manifold (SCM): 113.5 Metres 115.1 Metres
1.31	Distance bridge front to center of manifold: 75.5 Metres
1.32	Parallel body distances: Lightship Normal Ballast Summer Dwt
	Forward to mid-point manifold: 65.986 Metres 70.899 Metres 71.986 Metres
	Aft to mid-point manifold: 42.579 Metres 59.071 Metres 72.707 Metres
	Parallel body length: 109.781 Metres 129.415 Metres 144.693 Metres
1.33	FWA at summer draft / TPC immersion at summer draft: 333 Millimetres 67.08 Metric Tonnes
1.34	What is the max height of mast above waterline (air draft) Full Mast Collapsed Mast
	Lightship: 45.918 Metres 0.0 Metres
	Normal ballast: 41.075 Metres 0.0 Metres
	At loaded summer deadweight: 34.247 Metres 0.0 Metres
Tonnages	
1.35	Net Tonnage: 22,444
1.36	Gross Tonnage / Reduced Gross Tonnage (if applicable): 42,010
1.37	Suez Canal Tonnage - Gross (SCGT) / Net (SCNT): 44,162 39,772

1.38	Panama Canal Net Tonnage (PCNT):				34,705
Loadline Information					
1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	6.115 Metres	14.518 Metres	73,668.9 Metric Tonnes	89,343.7 Metric Tonnes
	Winter:	6.417 Metres	14.216 Metres	71,641.7 Metric Tonnes	87,316.5 Metric Tonnes
	Tropical:	5.813 Metres	14.82 Metres	75,702.2 Metric Tonnes	91,377 Metric Tonnes
	Lightship:	17.786 Metres	2.847 Metres		15,674.8 Metric Tonnes
	Normal Ballast Condition:	12.943 Metres	7.69 Metres	28,509.6 Metric Tonnes	44,184.6 Metric Tonnes
1.40	Does vessel have multiple SDWT?				No
1.41	If yes, what is the maximum assigned deadweight?				73,668.9 Metric Tonnes
Ownership and Operation					
1.42	Registered owner - Full style:			MT "Hellespont Promise" GmbH & Co. KG Kaiser-Wilhelm-Str. 9, D-20355 Hamburg, Germany Tel: +49 40 27 86 21 31 Fax: +49 40 27 86 21 30 Telex: VIA OPERATORS Email: operations@hellesponthammonia.de	
1.43	Technical operator - Full style:			HELLESPONT HAMMONIA GmbH & Co. KG Kaiser-Wilhelm-Str. 9, D-20355 Hamburg, Germany Tel: +49 40 27 86 21 31 Fax: +49 40 27 86 21 30 Email: operations@hellesponthammonia.de	
1.44	Commercial operator - Full style:			Hellespont Hammonia GmbH & Co. KG Kaiser-Wilhelm-Str. 9, D-20355 Hamburg, Germany Tel: +49 40 27 86 21 31 Fax: +49 40 27 86 21 30 Email: operations@hellesponthammonia.de	
1.45	Disponent owner - Full style:			Hellespont 7335 Corp. 80,Broad Street, Monrovia, Liberia	

2.	CERTIFICATION	Issued	Last Annual or Intermediate	Expires
2.1	Safety Equipment Certificate:	Dec 04, 2009	Dec 04, 2009	Jan 01, 2012
2.2	Safety Radio Certificate:	Jan 02, 2007	Nov 29, 2009	Jan 01, 2012
2.3	Safety Construction Certificate:	Mar 20, 2009	Nov 29, 2009	Jan 01, 2012
2.4	Loadline Certificate:	Jan 02, 2007	Nov 29, 2009	Jan 01, 2012
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Jun 17, 2008	Nov 29, 2009	Jan 01, 2012
2.6	Safety Management Certificate (SMC):	Mar 16, 2008	Jan 16, 2010	Jun 19, 2012
2.7	Document of Compliance (DOC):	Sep 22, 2009	Not Applicable	Nov 17, 2010
2.8	USCG (specify: COC, LOC or COI):			
2.9	Civil Liability Convention Certificate (CLC):	Feb 20, 2010		Feb 20, 2011
2.10	Civil Liability for Bunker Oil Pollution Damage Convention Certificate (CLBC):	Feb 20, 2010		Feb 20, 2011
2.11	U.S. Certificate of Financial Responsibility (COFR):	Jan 12, 2010		Jan 12, 2013
2.12	Certificate of Fitness (Chemicals):	Not Applicable	Not Applicable	Not Applicable
2.13	Certificate of Fitness (Gas):	Not Applicable	Not Applicable	Not Applicable
2.14	Certificate of Class:	Feb 22, 2007	Nov 29, 2009	Jan 01, 2012

2.15	International Ship Security Certificate (ISSC):	Mar 16, 2008	Jan 16, 2010	Jun 19, 2012
2.16	International Sewage Pollution Prevention Certificate (ISPPC)	Jan 02, 2007		Jan 01, 2012
2.17	International Air Pollution Prevention Certificate (IAPP):	Jan 02, 2007	Nov 29, 2009	Jan 01, 2012

Documentation

2.18	Does vessel have all updated publications as listed in the Vessel Inspection Questionnaire, Chapter 2- Question 2.24, as applicable:	Yes
2.19	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:	Yes

3.	CREW MANAGEMENT	
3.1	Nationality of Master:	Philippines
3.2	Nationality of Officers:	Filipino
3.3	Nationality of Crew:	Filipino
3.4	If Officers/Crew employed by a Manning Agency - Full style:	Officers: Manila Shipmanagement & Manning Inc. G/F & 2/F, Princess Building, 104 Esteban Street, Legaspi Village, Makati City 1229, Philippines Tel: +632 89 24 071 Fax: +632 81 66 993 Email: email@manship.com Crew: Manila Shipmanagement & Manning Inc. G/F & 2/F, Princess Building, 104 Esteban Street, Legaspi Village, Makati City 1229, Philippines Tel: + 632 892 4071 Fax: + 632 816 6993 Email: email@manship.com
3.5	What is the common working language onboard:	ENGLISH
3.6	Do officers speak and understand English:	Yes
3.7	In case of Flag Of Convenience, is the ITF Special Agreement on board:	Yes

4.	HELICOPTERS	
4.1	Can the ship comply with the ICS Helicopter Guidelines:	Yes
4.2	If Yes, state whether winching or landing area provided:	Winching

5.	FOR USA CALLS	
5.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter:	Yes
5.2	Qualified individual (QI) - Full style:	O'Brien's Response Management 103 Morgan Lane, Suite 103 Plainsboro, NJ 08536-3339 Tel: +1-609-2759600 Fax: +1-609-2759444 Email: info@obriensrm.com
5.3	Oil Spill Response Organization (OSRO) -Full style:	NATIONAL RESPONSE CORP. 3500 Sunrise Highway, Suite T-103, Great River, New York 11739, U.S.A. Tel: 001-631-2249141 Fax: 001-631-2249082
5.4	Has technical operator signed the SCIA / C-TPAT agreement with US customs concerning drug smuggling:	No

6.	CARGO AND BALLAST HANDLING	
Double Hull Vessels		
6.1	Is vessel fitted with centerline bulkhead in all cargo tanks:	Yes
6.2	If Yes, is bulkhead solid or perforated:	Solid
Cargo Tank Capacities		
6.3	Capacity (98%) of each natural segregation with double valve (specify tanks):	Seg #1: 28677.343 m3 (1W(P+S), 4W(P+S), SLOPS (P+S+RESIDUAL)) Seg #2: 28440.889 m3 (2W(P+S),5W(P+S))

		Seg #3: 27396.403 m3 (3W(P+S),6W(P+S))		
6.4	Total cubic capacity (98%, excluding slop tanks):	81,300.3 Cu. Metres (SLOPS 98%: 3159.05 m3 as follows: SLOPS(P+S): 2838.386m3 Residual: 320.660 m3.)		
6.5	Slop tank(s) capacity (98%):	3,153.5 Cu. Metres		
6.6	Residual/Retention oil tank(s) capacity (98%), if applicable:	320.66 Cu. Metres		
6.7	Does vessel have Segregated Ballast Tanks (SBT) or Clean Ballast Tanks (CBT):	SBT		
SBT Vessels				
6.8	What is total capacity of SBT?	25,310.7 Cu. Metres		
6.9	What percentage of SDWT can vessel maintain with SBT only:	35		
6.10	Does vessel meet the requirements of MARPOL Annex I Reg 18.2: (previously Reg 13.2)	Yes		
Cargo Handling				
6.11	How many grades/products can vessel load/discharge with double valve segregation:	3		
6.12	Maximum loading rate for homogenous cargo per manifold connection:	2,667 Cu. Metres/Hour		
6.13	Maximum loading rate for homogenous cargo loaded simultaneously through all manifolds:	8,000 Cu. Metres/Hour		
6.14	Are there any cargo tank filling restrictions. If yes, please specify:	No NA		
Pumping Systems				
6.15	Pumps:	No.	Type	Capacity
	Cargo:	3	Centrifugal	2300 M3/HR
	Stripping:	1	Reciprocating	250 Cu. Metres/Hour
	Eductors:	3	Other	250 Cu. Metres/Hour
	Ballast:	2	Centrifugal	1,500 Cu. Metres/Hour
6.16	How many cargo pumps can be run simultaneously at full capacity:	3		
Cargo Control Room				
6.17	Is ship fitted with a Cargo Control Room (CCR):	Yes		
6.18	Can tank innage / ullage be read from the CCR:	Yes		
Gauging and Sampling				
6.19	Can ship operate under closed conditions in accordance with ISGOTT:	Yes		
6.20	What type of fixed closed tank gauging system is fitted:	Radar		
6.21	Are overfill (high-high) alarms fitted? If Yes, indicate whether to all tanks or partial:	Yes All cargo tanks		
Vapor Emission Control				
6.22	Is a vapor return system (VRS) fitted:	Yes		
6.23	Number/size of VRS manifolds (per side):	2	400 Millimetres	
Venting				
6.24	State what type of venting system is fitted:	INDIVIDUAL PV VALVE/MAST RISER		
Cargo Manifolds				
6.25	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment':	Yes		
6.26	What is the number of cargo connections per side:	4		
6.27	What is the size of cargo connections:	400		
6.28	What is the material of the manifold:	STEEL		
Manifold Arrangement				
6.29	Distance between cargo manifold centers:	2,500 Millimetres		
6.30	Distance ships rail to manifold:	4,600 Millimetres		
6.31	Distance manifold to ships side:	4,600 Millimetres		
6.32	Top of rail to center of manifold:	750 Millimetres		
6.33	Distance main deck to center of manifold:	2,100 Millimetres		
6.34	Manifold height above the waterline in normal ballast / at SDWT condition:	15.33 Metres	8.42 Metres	
6.35	Number / size reducers:	6 x 400/300mm (16/12")		

		6 x 400/250mm (16/10") 6 x 400/200mm (16/8") 6 x 450/300mm (18/12") 6 x 450/250mm (18/10")		
Stern Manifold				
6.36	Is vessel fitted with a stern manifold:	No		
6.37	If stern manifold fitted, state size:	0 Millimetres		
Cargo Heating				
6.38	Type of cargo heating system?	Heating coils		
6.39	If fitted, are all tanks coiled?	Yes		
6.40	If fitted, what is the material of the heating coils:	Stainless Steel		
6.41	Maximum temperature cargo can be loaded/maintained:	66.0 °C / 150.8 °F 57 °C / 134.6 °F		
Tank Coating				
6.42	Are cargo, ballast and slop tanks coated?	Coated	Type	To What Extent
	Cargo tanks:	Yes	CMP Pure Epoxy Epicon T-500	Whole Tank
	Ballast tanks:	Yes	CMP Modified Epoxy NOVA 1000	Whole Tank
	Slop tanks:	Yes	CMP Pure Epoxy Epicon T-500	Whole Tank
6.43	If fitted, what type of anodes are used:	ZINC		

7.	INERT GAS AND CRUDE OIL WASHING	
7.1	Is an Inert Gas System (IGS) fitted:	Yes
7.2	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:	Flue Gas
7.3	Is a Crude Oil Washing (COW) installation fitted:	Yes

8.	MOORING					
8.1	Mooring wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	30 Millimetres	KAPANEEMA PLUS	220 Metres	64.4 Metric Tonnes
	Main deck fwd:	2	30 Millimetres	KAPANEEMA PLUS	220 Metres	64.4 Metric Tonnes
	Main deck aft:	2	30 Millimetres	KAPANEEMA PLUS	220 Metres	64.4 Metric Tonnes
	Poop deck:	4	30 Millimetres	KAPANEEMA PLUS	220 Metres	64.4 Metric Tonnes
8.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	72 Millimetres	Polyester/Polysteel	11 Metres	105 Metric Tonnes
	Main deck fwd:	2	72 Millimetres	Polyester/Polysteel	11 Metres	105 Metric Tonnes
	Main deck aft:	2	72 Millimetres	Polyester/Polysteel	11 Metres	105 Metric Tonnes
	Poop deck:	4	72 Millimetres	Polyester/Polysteel	11 Metres	105 Metric Tonnes
8.3	Mooring ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:		Millimetres		Metres	Metric Tonnes
	Main deck fwd:		Millimetres		Metres	Metric Tonnes
	Main deck aft:		Millimetres		Metres	Metric Tonnes
	Poop deck:		Millimetres		Metres	Metric Tonnes
8.4	Other mooring lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	5	60 Millimetres	Polyester/Polyolefin	220 Metres	70.5 Metric Tonnes
	Main deck fwd:		Millimetres		Metres	Metric Tonnes
	Main deck aft:		Millimetres		Metres	Metric Tonnes
	Poop deck:	5	60 Millimetres	Polyester/Polyolefin	220 Metres	70.5 Metric Tonnes
8.5	Mooring winches	No.			# Drums	Brake Capacity
	Forecastle:	2			Double Drums	48 Metric Tonnes
	Main deck fwd:	1			Double Drums	48 Metric Tonnes
	Main deck aft:	1			Double Drums	48 Metric Tonnes
	Poop deck:	2			Double Drums	48 Metric Tonnes
8.6	Mooring bitts	No.				SWL
	Forecastle:	4				64 Metric Tonnes
	Main deck fwd:	5				64 Metric Tonnes

	Main deck aft:	3	64 Metric Tonnes
	Poop deck:	8	64 Metric Tonnes
8.7	Closed chocks and/or fairleads of enclosed type	No.	SWL
	Forecastle:	8	64 Metric Tonnes
	Main deck fwd:	13	64 Metric Tonnes
	Main deck aft:	13	64 Metric Tonnes
	Poop deck:	15	64 Metric Tonnes

Emergency Towing System

8.8	Type / SWL of Emergency Towing system forward:	YT-2000	200 Metric Tonnes
8.9	Type / SWL of Emergency Towing system aft:	YT-2000	200 Metric Tonnes

Anchors

8.10	Number of shackles on port cable:	13
8.11	Number of shackles on starboard cable:	12

Escort Tug

8.12	What is SWL and size of closed chock and/or fairleads of enclosed type on stern:	64 Metric Tonnes	600
8.13	What is SWL of bollard on poopdeck suitable for escort tug:	64 Metric Tonnes	

Bow/Stern Thruster

8.14	What is brake horse power of bow thruster (if fitted):	0 bhp	0 Kilowatt
8.15	What is brake horse power of stern thruster (if fitted):	0 bhp	0 Kilowatt

Single Point Mooring (SPM) Equipment

8.16	Does vessel comply with the latest edition of OCIMF 'Recommendations for Equipment Employed in the Mooring of Vessels at Single Point Moorings (SPM)':	Yes	
8.17	Is vessel fitted with chain stopper(s):	Yes	
8.18	How many chain stopper(s) are fitted:	2	
8.19	State type of chain stopper(s) fitted:	Hinged Bar Type	
8.20	Safe Working Load (SWL) of chain stopper(s):	200 Metric Tonnes	
8.21	What is the maximum size chain diameter the bow stopper(s) can handle:	76 Millimetres	
8.22	Distance between the bow fairlead and chain stopper/bracket:	3,500 Millimetres	
8.23	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:	Yes	

Lifting Equipment

8.24	Derrick / Crane description (Number, SWL and location):	Cranes: 1 x 15 Tonnes, Midship	
8.25	What is maximum outreach of cranes / derricks outboard of the ship's side:	9 Metres	

Ship To Ship Transfer (STS)

8.26	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum or Liquefied Gas, as applicable):	Yes	
------	---	-----	--

9. MISCELLANEOUS

Engine Room

9.1	What type of fuel is used for main propulsion?	IFO 380	
9.2	What type of fuel is used in the generating plant?	IFO 380	
9.3	Capacity of bunker tanks - IFO and MDO/MGO:	1,875.8 Cu. Metres	242 Cu. Metres 0 Cu. Metres
9.4	Is vessel fitted with fixed or controllable pitch propeller(s)?	Fixed Pitch	

Insurance

9.5	P & I Club - Full Style:	BRITANNIA	
9.6	P & I Club coverage - pollution liability coverage:	1000000000	

Port State Control

9.7	Date and place of last Port State Control inspection:	Mar 04, 2009 / Le Havre	
9.8	Any outstanding deficiencies as reported by any Port State Control:	No	
9.9	If yes, provide details:	No outstanding deficiencies	

Recent Operational History

9.10	Has vessel been involved in a pollution, grounding, serious casualty or	Pollution: No, No	
------	---	-------------------	--

	collision incident during the past 12 months? If yes, full description:	Grounding: No , No Serious casualty: No , Collision: No , No
9.11	Last three cargoes / charterers / voyages (Last / 2nd Last / 3rd Last):	Please contact Owners for details
Vetting		
9.12	Date/Place of last SIRE Inspection:	Sep 09, 2009 / Amsterdam
9.13	Date/Place of last CDI Inspection:	
9.14	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: <i>* Blanket "approvals" are no longer given by Oil Majors and ships are accepted for the voyage on a case by case basis.</i>	BHP-RIGHTSHIP / SHELL / REPSOL / ADNOC / BP

Version 3 (